

DSP8063B 30W Wall Mount Speaker with Power Tap

Features



- Input 70V/100V/4-16Ω
- Wide Freq.Resp.:80Hz-20KHz
- Max SPL:105±2dB
- High sensitivity:90±2dB
- Wall mount type loudspeaker
- Metal grille and ABS enclosure of black color
- Equipped with hanging holes for mounting convenient

Description

The DSP8063 is a wall mount speaker built-in 70v/100v transformer. The 70v/100v transmission is realized in a high-voltage, low-current mode, which makes longer distance transmission and parallel connection of multiple loudspeakers possible.

Metal grille and ABS enclosure of black color, long-term durability, never out of shape and fading; high sensitivity, clear and sonorous sound. Easy and secure wall mount installation by hanging holes.

It is ideal choice for industrial and commercial applications in hotel, school, office and factory where background music and paging is needed.

Specification

Model	DSP8063	
Speaker Unit	5"×1, 1"×1	
Rated Power	30W	
Input	Constant voltage	70/100V
	Constant resistance	8Ω
Sensitivity(1M,1W)	90±2dB	
Max SPL(1M)	105±2dB	
Freq. Resp	80Hz-20kHz	
Weight	3.2 kg	
Dimension(H×W×D)	280×194×185mm	